



**NSK NUP2338EM cylindrical roller bearings**

Bearing No. NUP2338EM

NUP2338EM Bearing 2D drawings and 3D CAD models

Size	190x400x132 mm
Bore Diameter	190 mm
Outer Diameter	400 mm
Width	132 mm
d	190 mm
Fw	240 mm
D	400 mm
B	132 mm
C	132 mm
r min.	5 mm
r1 min.	5 mm
da min.	210 mm
Da max.	380 mm
db max.	235 mm
db min	210 mm
ra max.	4 mm
rb max.	4 mm
S	6,2 mm
Db max	380 mm
Weight	86,2 Kg
Basic dynamic load rating (C)	1770 kN
Basic static load rating (C0)	2520 kN
(Grease) Lubrication Speed	1300 r/min
hidYobi	NUP2338EM
LangID	1
D_	400



## TLEE Bearing Machine Development Co.,...

Macha rpm	2000
B_	132
hidTable	ecat_NSCLDR
Oil rpm	1600
rb	4
mass	88.1
GRS rpm	1300
ra	4
db max	235
TSR rpm	1400
C0	2520
DE_	352
Prod_Type3	CRB_SR_NUP
da	210
DA_	56
Z_	14
D_a max	380
yobi	NUP2338EM
dd min	268
C_conv	1770000
ALPHA_	0
SDM_	296
r	5
dc min	248
KBRG	4165
SBRG	23
r1	5
DI_	240