



NSK 6030ZZ deep groove ball bearings

Bearing No. 6030ZZ

6030ZZ Bearing 2D drawings and 3D CAD models

Size	150x225x35 mm
Bore Diameter	150 mm
Outer Diameter	225 mm
Width	35 mm
d	150 mm
D	225 mm
B	35 mm
C	35 mm
r min.	2,1 mm
da min.	161 mm
da max	170 mm
Da max.	214 mm
ra max.	2 mm
Weight	4,24 Kg
Basic dynamic load rating (C)	126 kN
Basic static load rating (C0)	126 kN
(Grease) Lubrication Speed	2 600 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.52
EAN	0029176020322
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0



TLEE Bearing Machine Development Co.,...

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	150MM Bore; 225MM Outside Diameter; 35MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6030ZZ
Weight / LBS	4.1
Outer Race Width	1.378 Inch 35 Millimeter
Outside Diameter	8.858 Inch 225 Millimeter
Bore	5.906 Inch 150 Millimeter
SRI	11.5
hidYobi	6030ZZ
LangID	1
D_	225
SREX	0.04
B_	35
da min	161



TLEE Bearing Machine Development Co.,...

hidTable	ecat_NSRDGB
SRE	11.5
mass	4.24
GRS rpm	2600
ra	2
SRIX	0.04
D_a	214
SRIN	-0.04
C0	126
fo	15.9
SREN	-0.04
DE_	209.725
Prod_Type3	DGBB_SR_ZZ
DA_	22.225
bomp	0
Z_	16
yobi	6030ZZ
C_conv	126000
ALPHA_	0
SDM_	187.5
r	2.1
KBRG	6141
SBRG	10
DI_	165.275